



- Easy to use
- Easily installed
- Space saving
- Wall-mounted
- Rear wheel locking point
- Hot dip galvanised finish
- Suitable for fixing to uneven walls

Options

- Available with unique triple locking mechanism securing both wheels and frame to rack
- Available with supporting frame for any quantity
- Available with powder coated finish in a standard colour of your choice
- Available in stainless steel

The **Carlisle CycleRax** allows cycles to be parked in 40% less space than horizontal systems.

The **Carlisle CycleRax** is ideal for use at home, bike rooms, student residences and underground car parks indeed wherever space is at a premium.

CycleRax Limited

Thornbank 38 Moorgate Road Rotherham S60 2AG

T: 01709 378644 F: 01709 480555 E: service@cyclerax.com W: www.cyclerax.com

Specification

Material:	Mild steel
Finish:	Hot dip galvanised
Dimensions:	Height: 1829mm
	Width: 100mm
	Depth: 1145mm
	Weight: 8kg

Installation

Spacing:	End Racks: 305mm from side wall
	Centres: 300mm minimum
	A minimum distance from the wall of 1145mm is required to accommodate the cycle and a further minimum corridor width of 1000mm (recommended 1500mm) is required for access.

Height requirements: A minimum ceiling height of 1900mm is required.

Fastenings:	Use M6 50mm Anker bolts or M6 60mm long shield anchor bolts, for concrete or brick walls, which we can supply at extra cost. The rack should be fixed to the wall via the top fixing hole and to the ground through the two fixing holes at the bottom.
-------------	---

The dimensions of a standard cycle are:

Length:	1830mm
Height:	990mm
Width:	584mm (vary between 559mm and 660mm)
Weight:	13.5kg

Security

The **Carlisle CycleRax** is designed to be used with the cyclists own D-lock or Cable-lock.

The **CycleRax** triple locking mechanism is an optional extra where security is paramount.

CycleRax Limited

Thornbank 38 Moorgate Road Rotherham S60 2AG

T: 01709 378644 F: 01709 480555 E: service@cyclerax.com W: www.cyclerax.com